

## SABIC® HDPE T5E01BW

## HIGH DENSITY POLYETHYLENE FROM TRUCIRCLE™ PORTFOLIO **REGION EUROPE**

## **DESCRIPTION**

SABIC® HDPE T5E01BW White is a polyethylene resin, which is formulated with 50% post-consumer recycled plastics. The grade is part of SABIC's TRUCIRCLE™ portfolio and services. It can be used for blow molding of consumer packaging up to 5 l for household and industrial chemicals, such as detergents, cleaners, shampoos and

This product is not intended for and must not be used in any pharmaceutical/medical applications.

## **TYPICAL PROPERTY VALUES**

PROPERTIES	TYPICAL VALUES	UNITS	TEST METHODS
POLYMER PROPERTIES			
Melt Flow Rate (MFR)			
at 190 °C and 2.16 kg	0.2	dg/min	ISO 1133
at 190 °C and 5 kg	0.8	dg/min	ISO 1133
at 190 °C and 21.6 kg	24	dg/min	ISO 1133
Density (1)	968	kg/m³	ISO 1183
MECHANICAL PROPERTIES (1) (2)			
Izod impact notched			
at 23 °C	10	kJ/m²	ISO 180/A
ESCR (10% Igepal CO-630), F50	50	h	ASTM D1693B

<sup>(1)</sup> Compression moulding of test specimen according to ISO 1872-2

<sup>(2)</sup> Conditioning of test specimen: temp. 23 °C, relative humidity 50 %, 24 hours