



Braskem PP FPT350WV3

Braskem America Inc. - Polypropylene Homopolymer

General Information

Product Description

Narrow molecular weight distribution, antistatic, nucleated, very good mold release

Applications
Suggested uses include fast-cycle injection molding, large-part injection molding, disposable drinkware

General

Additive	- Antistatic - Nucleating Agent
Features	- Antistatic - Fast Molding Cycle - Good Mold Release - Narrow Molecular Weight Distribution - Nucleated
Uses	Disposable Drinkware
Agency Ratings	FDA 21 CFR 177.1520
Processing Method	Injection Molding

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	35	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength ² (Yield)	37.9	MPa	ASTM D638
Tensile Elongation ² (Yield)	8.0	%	ASTM D638
Flexural Modulus - 1% Secant ³	1650	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	27	J/m	ASTM D256A
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	106		ASTM D785

