

**Product Description**

*Integrate* products are chemically modified polyolefins used to combine dissimilar materials for a variety of applications including molded articles, flexible materials and fiber technology or to provide property enhancements which fulfill final material parameters. These products are particularly effective when the materials involved contain both polar and non-polar components. Specific ingredients may include polymers such as polyethylene and/or its copolymers, polypropylene and/or its copolymers, polyamides (nylon), polyacetates, cellulose, wood flour as well as a variety of minerals, which can be used to improve strength or stiffness of the final composition. *Integrate* products are available in pellet form.

<b>Application</b>	Wire & Cable; Wood Composites
<b>Market</b>	Compounding; Coupling Agents; Industrial, Building & Construction; Wire & Cable
<b>Processing Method</b>	Sheet and Profile Extrusion; Wire & Cable

Typical Properties	Nominal Value	Units	Test Method
<b>Physical</b>			
Melt Flow Rate, (190 °C/2.16 kg)	13	g/10 min	ASTM D1238
Density, (23 °C)	0.943	g/cm <sup>3</sup>	ASTM D1505
<b>Mechanical</b>			
Flexural Modulus, (1% Secant)	552	MPa	ASTM D790
Tensile Strength at Break	15.3	MPa	ASTM D638
Tensile Elongation at Break	650	%	ASTM D638
<b>Thermal</b>			
Vicat Softening Point	106	°C	ASTM D1525

