



## Hifax TYC 1229P

### Compounded Polyolefin

#### Product Description

Hifax TYC 1229P is a high flow thermoplastic polyolefin designed for automotive and heavy-truck applications that require energy management combined with ductility, stiffness and impact resistance over a broad temperature range. This material exhibits excellent processability and dimensional stability.

#### Product Characteristics

Test Method used	ISO
Processing Methods	Injection Molding
Features	Good Dimensional Stability, Low Temperature Impact Resistance, Good Processability, Good Stiffness
Typical Customer Applications	Bumpers, Exterior Applications

Typical Properties	Method	Value	Unit
<b>Physical</b>			
Density (Method A)	ISO 1183	1.16	g/cm <sup>3</sup>
Melt flow rate (MFR) (230°C/2.16Kg)	ISO 1133	27	g/10 min
<b>Mechanical</b>			
Tensile Stress at Yield (23°C)	ISO 527-1, -2	17	MPa
Flexural modulus (2 mm/min)	ISO 178	2500	MPa
<b>Impact</b>			
Notched Izod Impact (23°C)	ASTM D 256	35	kJ/m <sup>2</sup>
<b>Additional Information</b>			
Mold shrinkage	ISO 294-4		
<i>Note: Please contact LyondellBasell for shrinkage recommendations.</i>			

#### Notes

Typical properties; not to be construed as specifications.

