

Adflex Q 401 F

Advanced Polyolefin

Product Description

Adflex Q 401 F is a reactor TPO (thermoplastic polyolefin) manufactured using LyondellBasell's proprietary *Catalloy* process technology. It is suitable for air quenched blown film applications. It contains slip and anti-block additives.

For regulatory compliance information, see the Adflex Q 401 F Product Stewardship Bulletin (PSB).

Product Characteristics

Status	Commercial: Active
Test Method used	ISO
Features	High Heat Resistance , Good Puncture Resistance , Good Tear Strength
Typical Customer Applications	Blown Film, Film

Typical Properties	Method	Value	Unit
Physical			
Density (Method A)	ISO 1183	0.89	g/cm ³
Melt flow rate (MFR) (230 °C/ 2.16 kg)	ISO 1133	0.65	g/10 min
Mechanical			
Tensile Stress at Break (23 °C)	ISO 527-1, -2	21	MPa
Tensile Stress at Yield (23 °C)	ISO 527-1, -2	15	MPa
Tensile Strain at Break (23 °C)	ISO 527-1, -2	>800	%
Tensile Strain at Yield (23 °C)	ISO 527-1, -2	27	%
Flexural modulus (23 °C)	ISO 178	480	MPa
Impact			
Notched izod impact strength	ISO 180		
(- 40°C, Type 1, Notch A)		4	kJ/m ²
(23°C, Type 1, Notch A)		60	kJ/m ²
Hardness			
Shore hardness D	ISO 868/ASTM D 2240	49	
<i>Note: 15 seconds</i>			
Thermal			
Heat deflection temperature B (0.45 MPa) Unannealed	ISO 75B-1, -2	57	°C
Melting temperature	DSC	164	°C
Vicat softening temperature A/50	ISO 306	108	°C

