

Product name: **POLYLAC® MABS**

Version 5

**Section 1. Identification of the substance/ mixture and of the company/ undertaking**

**1.1 Product identifier**

Product name: **POLYLAC®**

This safety data sheet pertains to the following products: PA-758, PA-758R

**1.2 Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses: Mixture used for the production of molded plastic articles

**1.3 Details of the supplier of the Safety Data Sheet**

Supplier: CHIMEI Corporation

Address: No. 398, Sec. 1, Zhongzheng Rd., Rende Dist., Tainan City, 717010, Taiwan

Telephone: +886 6 2663000 Ext. 1347

**1.3 Emergency telephone number**

Emergency telephone : +886 6 2663000 Ext. 2501

**Section 2. Hazards identification**

**2.1 Classification of the substance or mixture**

Classification according to Directive 67/548/EEC or 1999/45/EC: Not classified as hazardous (polymeric state)

Classification according to Regulation (EC) N° 1272/2008 (CLP): Not classified as hazardous (polymeric state)

**2.2 Label elements**

Not labelled as hazardous

Classification according to Regulation (EC) N° 1272/2008 (CLP): Not classified as hazardous (polymeric state)

**2.3 Other hazards**

vPvB/PBT assessment: not available

Swallowing may cause gastrointestinal irritation and pain of guts.

**Section 3. Composition/information on ingredients**

**3.1 Composition of the substance/ preparation**

Substance or Preparation Substance

CAS	Name	content
9010-94-0	Methyl methacrylate-Acrylonitrile-Butadiene-Styrene Copolymer	> 98 %
-	Additives	≤ 2 %

Impurities Contributing to Hazard: None

Product name: **POLYLAC ® MABS**

Version 5

**3.2 Additional information: -**

Reach Info:

	Registration No.
Acrylonitrile	01-2119474195-34-0045
Styrene	01-2119457861-32-0006
	01-2119457861-32-0007
	01-2119457861-32-0057
	01-2119457861-32-0065
	01-2119457861-32-0081
Buta-1,3-diene	01-2119471988-16-0044
Methyl methacrylate	01-2119452498-28-0011
	01-2119452498-28-0016

**3.3 For full text of R- and H-phrases: see section 16**

**Section 4. First-aid measures**

**4.1 Description of first aid measures**

General notes: Remove affected persons from the danger area, at the same time ensuring your own safety. Remove all contaminated clothing immediately

Following inhalation: In case of gases evolving from melted resin, move subject to fresh air. Treat symptomatically

Following skin contact: In case of pellets or powder, wash with water. In case of smelt, wash affected skin area and clothing with plenty of (soap and) water. Seek medical advice

Following eye contact: In case of pellets or powder, flush with plenty of water for at least 15 minutes. Seek medical advice if any dust particles still remain.

In case of gases evolving from melted resin of high temperature, flush with plenty of water for at least 15 minutes. Seek medical advice if necessary

Following ingestion: Induce vomiting. Rinse mouth with water. Seek medical advice if necessary

**4.2 Most important symptoms & effects both acute & delayed**

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

**4.3 Indication of any immediate medical attention and special treatment needed: -**

If burn is present, treat as any thermal burn, after decontamination. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

**Section 5. Fire-fighting measures**

**5.1 Extinguishing media**

Suitable extinguishing agents: water spray, dry powder, foam, carbon dioxide  
Dry chemical, carbon dioxide, regular foam extinguishing agent, spray

**5.2 Special hazards arising from the substance or mixture: -**

Hazardous Combustion Products: During a fire, smoke may contain the original material in addition to

Product name: **POLYLAC ® MABS**

Version 5

combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Phenolic compounds.

Unusual Fire and Explosion Hazards: Pneumatic conveying and other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, do not permit dust to accumulate. Dense smoke is emitted when burned without sufficient oxygen.

### 5.3 Advice for firefighters

Fire fighting instructions: Keep people away. Isolate fire area and de unnecessary entry. Cool surroundings with water to localize fire zone. Soak thoroughly with water to cool and prevent re-ignition. Pellets or powder remained on ground may cause slipping.

Protective equipment: Protective fire fighting clothing (including fire fighting helmet, coat, pants, boots, and gloves), positive-pressure self contained breathing apparatus (SCBA).

### 5.4 Additional information: -

## Section 6. Accidental release measures

### 6.1 Personal precautions, protective equipment & emergency procedures

Keep out of irrigation ditches, sewers, and water supplies. Spills should be collected to prevent contamination of waterways  
Isolate area. Wear protective equipment. Ensure adequate ventilation. Keep away from ignition sources. Keep unprotected persons away.

### 6.2 Environmental precautions

Gather pellets and powder thoroughly to avoid birds or fishes taking from draining water.  
Do not allow product to reach sewage system or water bodies. Inform respective authorities in case product reaches water, sewage system or soil

### 6.3 Methods and material for containment and cleaning up

Contain spilled material if possible. Sweep up. Collect in suitable and properly labeled containers.

### 6.4 Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

## Section 7. Handling and storage

### 7.1 Precautions for safe handling

Handling Procedures: No smoking, open flames or sources of ignition in handling and storage area.  
Good housekeeping and controlling of dusts are necessary for safe handling of product. Avoid breathing process fumes. Use with adequate ventilation.

When appropriate, unique handling information for containers can be found on the product label.  
Workers should be protected

from the possibility of contact with molten resin. Do not get molten material in eyes, on skin or clothing. Pneumatic conveying and

other mechanical handling operations can generate combustible dust. To reduce the potential for dust explosions, electrically

bond and ground equipment and do not permit dust to accumulate. Dust can be ignited by static discharge.

Product name: **POLYLAC ® MABS**

Version 5

## 7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions: Keep the material at a cool dry place. Protect from direct sunlight, rain and violent temperature fluctuation. Fire is inhibited around storage area.

## 7.3 Specific end use(s)

Recommendations: -

# Section 8. Exposure controls/personal protection

## 8.1 Control parameters

Exposure Limits: Although some of the additives used in this product may have exposure guidelines, these additives are encapsulated in the product and no exposure would be expected under normal handling conditions.

## 8.2 Exposure control

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Personal protection:

- Respiratory protection: Wear masks for cleaning molding machines
- Hand protection: Heat-insulating gloves when handling molten form
- Eye protection: Wear safety glasses for general purpose. Wear chemical goggles for cleaning molding machines
- Skin and body protection: Gloves necessary for handling melted resin
- Hygiene measures: Wash hands after handling

## 8.3 Environmental exposure controls

Product related measures to prevent exposure: None specific

Instruction measures to prevent exposure: None specific

Organizational measures to prevent exposure: None specific

Technical measures to prevent exposure: None specific

Environmental exposure controls: Do not allow product to reach sewage system or water bodies

# Section 9. Physical and chemical properties

## 9.1 Information on basic physical and chemical properties

Appearance	Transparent pellet
Odour	Odourless
Colour	Transparent
Odour threshold	Not determined
pH	Not applicable
Melting point / freezing point	Not applicable
Initial boiling point and boiling range	Not applicable
Flash point	> 400°C
Evaporation rate (Butyl Acetate = 1)	Not applicable
Flammability (solid, gas)	Not available
Upper/lower flammability or explosive limits	Not applicable
Vapour pressure	Not applicable
Vapour density (air = 1)	Not applicable
Relative density (H <sub>2</sub> O = 1)	about 1.03 - 1.10 g/cm <sup>3</sup>
Bulk density	Not determined

Product name: **POLYLAC ® MABS**

Version 5

Solubility in water (by weight)	Insoluble
Partition coefficient (n-octanol/water)	Not applicable
Auto-ignition temperature	> 400°C
Decomposition temperature	> 280°C
Viscosity	Not applicable
Explosive properties	Not explosive
Oxidizing properties	Not oxidizing

9.2 **Other safety information:** No test data available

## Section 10. Stability and reactivity

**10.1 Reactivity:** Non-reactive under normal handling and storage conditions

**10.2 Chemical stability:** Stable under normal handling and storage conditions

**10.3 Possible hazardous reaction:** Polymerization will not occur.

**10.4 Conditions to avoid:** Avoid temperatures above 300 °C. Exposure to elevated temperatures can cause product to decompose.

**10.5 Incompatible materials:** Strong oxidizing agents, Gasoline, aldehydes, ketone

**10.6 Hazardous decomposition products:** Decomposition products depend upon temperature, air supply and the presence of other materials. Processing may release fumes and other decomposition products. At temperatures exceeding melt temperatures, polymer fragments can be released. Fumes can be irritating. Decomposition products can include and are not limited to: Combustible gases. In case of fire may be liberated: smoke, acrylonitrile monomer, styrene-monomer, methyl methacrylate monomer, aldehydes and acids (organic), carbon monoxide and carbon dioxide (CO<sub>2</sub>), hydrogen cyanide (HCN), nitrogen monoxide (NO).

## Section 11. Toxicological information

### 11.1 Information on toxicological effects

#### Toxicological effects:

- Acute toxicity (oral): Based on available data, the classification criteria are not met. Mild acute toxicity
- Acute toxicity (dermal): Based on available data, the classification criteria are not met. Mild acute toxicity
- Acute toxicity (inhalative): Based on available data, the classification criteria are not met. Mild acute toxicity
- Skin corrosion/irritation: Lack of data. May cause irritations.
- Eye damage/irritation: Lack of data. May cause irritations.
- Sensitisation to the respiratory tract: Lack of data. The chemical structure does not suggest a specific alert for such an effect.
- Skin sensitisation: Based on available data, the classification criteria are not met. Not sensitizing
- Germ cell mutagenicity/Genotoxicity: Lack of data. The chemical structure does not suggest a specific alert for such an effect.
- Carcinogenicity: Based on available data, the classification criteria are not met.
- Reproductive toxicity: Lack of data. The chemical structure does not suggest a specific alert for such an effect.
- Effects on or via lactation: Lack of data.
- Specific target organ toxicity (single exposure): Lack of data.

Product name: **POLYLAC ® MABS**

Version 5

- Dusts: Can cause skin, eye and respiratory tract irritation.
- Specific target organ toxicity (repeated exposure): Lack of data.
- Processing, thermal hazards: Vapours: Can cause skin, eye and respiratory tract irritation.

Symptoms

- Dust: Can cause skin, eye and respiratory tract irritation.
- The melted product can cause severe burns.
- Irritating to eyes, respiratory system and skin.
- In case of ingestion: Swallowing may cause gastrointestinal irritation and pain of guts.

**Section 12. Ecological information**

**12.1 Toxicity**

Not expected to be acutely toxic, but material in pellet or bead form may mechanically cause adverse effects if ingested by waterfowl or aquatic life.

**12.2 Persistence and degradability**

This water-insoluble polymeric solid is expected to be inert in the environment. Surface photodegradation is expected with exposure to sunlight. No appreciable biodegradation is expected.

**12.3 Bioaccumulative potential**

To avoid bioaccumulation plastics should not be disposed in the sea or in other water environments.

**12.4 Mobility in soil**

In the terrestrial environment, material is expected to remain in the soil. In the aquatic environment, material will sink and remain in the sediment.

**12.5 Results PBT & vPvB assessment**

According to the revised Annex XIII of regulation (EC) 1907/2006 and (EC) 253/2011: No information available on the product as such

**12.6 Other adverse effects:**

General information: Do not allow to enter into ground-water, surface water or drains.

**12.7 Additional information: -**

**Section 13. Disposal considerations**

**13.1 Waste treatment methods**

After containers have been emptied as thoroughly as possible (e.g. by pouring, scraping or draining until "drip-dry"), they can be sent to an appropriate collection point set up within the framework of the existing take-back scheme of the chemical industry. Containers must be recycled in compliance with national legislation and environmental regulations.

The product is suitable for mechanical recycling. After appropriate treatment it can be remelted and reprocessed into new moulded articles. Mechanical recycling is only possible if the material has been selectively retrieved and carefully segregated according to type.

Product name: **POLYLAC ® MABS**

Version 5

**Section 14. Transport information**

**ADR/RID**

**14.1 UN number**

Not applicable

**14.2 UN proper shipping name**

Proper Shipping Name: NOT REGULATED

**14.3 Transport hazard class(es)**

Not applicable

**14.4 Packing Group**

Not applicable

**14.5 Environmental hazards**

Not considered environmentally hazardous based on available data

**14.6 Special precautions for user**

Special Provisions: no data available

Hazard identification No: no data available

**ADNR / ADN**

**14.1 UN number**

Not applicable

**14.2 UN proper shipping name**

Proper Shipping Name: NOT REGULATED

**14.3 Transport hazard class(es)**

Not applicable

**14.4 Packing Group**

Not applicable

**14.5 Environmental hazards**

Not considered environmentally hazardous based on available data

**14.6 Special precautions for user**

No data available

**IMDG**

**14.1 UN number**

Not applicable

**14.2 UN proper shipping name**

Proper Shipping Name: NOT REGULATED

**14.3 Transport hazard class(es)**

Not applicable

**14.4 Packing Group**

Not applicable

**14.5 Environmental hazards**

Not considered environmentally hazardous based on available data

**14.6 Special precautions for user**

EMS Number: Not applicable

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

**ICAO/IATA**

**14.1 UN number**

Not applicable

**14.2 UN proper shipping name**

Proper Shipping Name: NOT REGULATED



Product name: **POLYLAC ® MABS**

Version 5

**14.3 Transport hazard class(es)**

Not applicable

**14.4 Packing Group**

Not applicable

**14.5 Environmental hazards**

Not considered environmentally hazardous based on available data

**14.6 Special precautions for user**

no data available

**Section 15. Regulatory information**

**15.1 Safety, health and environmental regulations /legislation specific for the substance or mixture**

Authorization and / or restrictions on use: None

**15.2 Chemical Safety Assessment**

For this substance a chemical safety assessment is not yet required.

**Section 16. Other information**

**16.1 Indication of changes**

Version 1: First issue according to Regulations (EC) 1907/2006 (REACH) and 1272/2008 (CLP)

**16.2 Abbreviations and acronyms**

AGS	Ausschuss für Gefahrstoffe	LoW	List of Waste
AF	Assessment Factor	MARPOL	MARine POLLution
BCF	BioConcentration Factor	MIE	Minimum Ignition Energy
CAS	Chemical Abstract Service	N°EC	European Commission number
CMR	Carcinogenic, Mutagenic and Reprotoxic	NFPA	National Fire Protection Association
CSR	Chemical Safety Report	NIOSH	National Institute of Occupational Safety and Health
DFG	German Research Foundation	NOEC	No Observed Effect Concentration
DNEL	Derived No Effect Level	NOELR	No Observed Effect Loading Rate
EC	European Commission	OECD	Organisation for Economic Co-operation and Development
EC50	Effective Concentration (required to induce a 50% effect)	OEL	Occupational Exposure Limit
EEC	European Economic Community	OSHA	Occupational Safety and Health Administration
EWC	European Waste Catalogue Code	PBT	Persistent Bioaccumulable Toxique
IDLH	Immediately Dangerous to Life or Health	PNEC	Previsible Non Effect Concentration
IBC	International Bulk Chemical	QSAR	Quantitative Structure-Activity Relationship
Koc	Soil/Water Partition Coefficient	STOT	Specific Target Organ Toxicity
Kow	Octanol/Water Partition Coefficient	TCLo	Toxic Concentration Low
LC50	Lethal Concentration 50	TDLo	Toxic Dose Low
LD50	Lethal Dose 50	UN	United Nations
LEL	Lower Explosive Limit	UVCB	Unknown or Variable Composition Complex Reaction Products, or Biological Materials
LL100	Lethal Loading	vPvB	very Persistent, very Bioaccumulative
LOEC	Lowest Observed Effect Concentration		



Product name: **POLYLAC ® MABS**

Version 5

**16.3 Key literature references and sources for data**

<http://esis.jrc.ec.europa.eu/>  
<http://echa.europa.eu/>  
<http://gestis-en.itrust.de>

**16.4 Training advice: -**

**16.5 Further information:**

According to the guidance version 2.0 for monomers and polymers from the European Chemicals Agency dated as of April 2012, the classification of the polymer takes into account the classification of all its constituents, such as unreacted monomers. These constituents in fact should be taken into account for classification of the polymer. This means that the same classification methods as for mixture should be applied to polymer substances.

In order to determine a classification for the studies about the water soluble fraction as well as the absorption should be performed on the polymer as such.

*To the best of our knowledge and belief, the information contained herein is accurate and obtained from sources believed to be reliable. No representation is made that the information is complete or the material is suitable for all purposes. The final determination as to the suitability of the user's intended use of the material is the sole responsibility of the user. All materials may present unknown hazards even when used in common applications and accordingly, it is the sole responsibility of the user to understand and address all potential hazards, including those identified herein. The information set forth in Sections 11 and 12 reflects data available as of the date hereof. It is anticipated that such data will be updated.*