

# PLATAMID®

# H 1937 PELLETS

## Platamid® H 1937 Pellets

Copolyamide Hot Melt Adhesive / Extrusion Applications

**Platamid® H 1937** is a thermoplastic copolyamide adhesive available in pellet form for manufacture of hot melt film and webs by extrusion.

**Platamid® H 1937** has good adhesion to all kinds of textile substrates based on native and synthetic fibers.

PROPERTIES	DRY / COND	UNIT	TEST STANDARD
RHEOLOGICAL PROPERTIES			
Melt Volume-Flow Rate	18 / *	cm <sup>3</sup> /10min	ISO 1133
Temperature	160 / *	°C	-
	320 / *	°F	-
Load	2.16 / *	kg	-
	4.76 / *	lb	-
THERMAL PROPERTIES			
Melting Temperature, 10°C/min	102 / *	°C	ISO 11357-1/-3

## AVAILABLE GRADES

This product is available:

- dried (H 1937 TA)

## PACKAGING

- Platamid® H 1937 TA is delivered in 25 kg sealed bags.

This grade is ready to be processed.

## SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

<b>PROCESSING</b> Film Extrusion, Web Processing	
<b>DELIVERY FORM</b> Pellets	
<b>SPECIAL CHARACTERISTICS</b> Adhesive	
<b>REGIONAL AVAILABILITY</b> North America, Europe, Asia Pacific, South and Central America, Near East/Africa	