

PLATAMID®

H 38 PELLETS

Platamid® H 38 Pellets

Copolyamide Hot Melt Adhesive

Platamid® H 38 is a standard thermoplastic copolyamide hot melt adhesive available in pellet form. This low to medium melt viscosity grade is particularly suitable for manufacturing webs, nets, mono- and multi-filaments and films by extrusion.

Platamid® H 38 offers very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc).

PROPERTIES	DRY / COND	UNIT	TEST STANDARD
RHEOLOGICAL PROPERTIES			
Melt Volume-Flow Rate	23 / *	cm³/10min	ISO 1133
Temperature	160 / *	°C	-
	320 / *	°F	-
Load	2.16 / *	kg	-
	4.76 / *	lb	-
THERMAL PROPERTIES			
Melting Temperature, 10°C/min	109 / *	°C	ISO 11357-1/-3
OTHER PROPERTIES			
Density	1.07 / 1.07	kg/m³	ISO 1183
	0.00107 / 0.00107	g/cm³	

AVAILABLE GRADES

This grade is available:

- dried with optical brightener (H 38 TA)
- undried with optical brightener (H 38 FA)

PACKAGING

Platamid® H 38 TA is delivered in 25 kg sealed bags.

Platamid® H 38 FA is delivered in 500 kg sealed big bags (GRVS).

These grades are ready to be processed

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

PLATAMID®

H 38 PELLETS

PROCESSING Web Processing	
DELIVERY FORM Pellets	
REGIONAL AVAILABILITY North America, Europe, Asia Pacific, South and Central America, Near East/Africa	