

PLATAMID®

H 2528 POWDER

Platamid® H 2528 Powder

Copolyamide Hot Melt Adhesive / Textile Applications

Platamid® H 2528 Powder is a medium melt viscosity copolyamide adhesive powder for the production of fusible interlinings. **Platamid® H 2528 Powder** offers excellent laundry resistance up to 60°C and an excellent steam resistance at moderate fusing conditions.

PROPERTIES	DRY / COND	UNIT	TEST STANDARD
RHEOLOGICAL PROPERTIES			
Melt Volume-Flow Rate	44 / *	cm ³ /10min	ISO 1133
Temperature	160 / *	°C	-
	320 / *	°F	-
Load	2.16 / *	kg	-
	4.76 / *	lb	-
THERMAL PROPERTIES			
Melting Temperature, 10°C/min	128 / *	°C	ISO 11357-1/-3

AVAILABLE GRADES

This grade is available in different grain sizes:

- Platamid® H 2528 PA80 (0-80 µm paste dot)
- Platamid® H 2528 PTA 120 (0-120 µm power dot)
- Platamid® H 2528 PTA 170/20 (0-170 µm power dot)
- Platamid® H 2528 PTA 170 (80-170 µm double dot)

PACKAGING

Platamid® H 2528 PTA 170, Platamid ® H 2528 PA80, Platamid ® H 2528 PTA 120 and Platamid ® H 2528 PTA 170/20 are delivered in 20 kg sealed bags.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

PLATAMID®

H 2528 POWDER

PROCESSING Scattering, Paste, Double Dot	
DELIVERY FORM Powder	
SPECIAL CHARACTERISTICS Adhesive	
REGIONAL AVAILABILITY North America, Europe, Asia Pacific, South and Central America, Near East/Africa	