

# PLATAMID®

# H 2516 PELLETS

## Platamid® H 2516 Pellets

Copolyamide Hot Melt Adhesive

**Platamid® H 2516** is a thermoplastic copolyamide hot melt adhesive available in pellet form. This fast re-crystallizing grade has been developed to manufacture hot-melt webs, nets and mono- and multi-filaments.

**Platamid® H 2516** offers a very good adhesion to all kinds of textile substrates based on native and synthetic fibers. Additionally **Platamid® H 2516** provides elastomeric properties and high water vapor transmission rate.

PROPERTIES	DRY / COND	UNIT	TEST STANDARD
RHEOLOGICAL PROPERTIES			
Melt Volume-Flow Rate	85 / *	cm³/10min	ISO 1133
Temperature	160 / *	°C	-
	320 / *	°F	
Load	2.16 / *	kg	-
	4.76 / *	lb	
THERMAL PROPERTIES			
Melting Temperature, 10°C/min	108 / *	°C	ISO 11357-1/-3

## AVAILABLE GRADES

This grade is available:

- Undried with optical brightener (H 2516 FA)

## PACKAGING

Platamid® H 2516 FA is delivered in 500 kg sealed bags (GRVS) and 500 kg sealed rigid container (GRVC). These grades are ready to be processed.

## SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

<b>PROCESSING</b>	
Melt Spinning	
<b>DELIVERY FORM</b>	
Pellets	
<b>SPECIAL CHARACTERISTICS</b>	
Adhesive	
<b>REGIONAL AVAILABILITY</b>	
North America, Europe, Asia Pacific, South and Central America, Near East/Africa	