

PLATAMID®

HX 2598 PELLETS

Platamid® HX 2598 Pellets

Copolyamide Hot Melt Adhesive / Extrusion Applications

Platamid® HX 2598 is a standard thermoplastic copolyamide hot melt adhesive available in pellet form. This medium melt viscosity grade is particularly suitable for manufacturing webs, nets, mono- and multi-filaments, and films by extrusion.

Platamid® HX 2598 offers a very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc).

PROPERTIES	DRY / COND	UNIT	TEST STANDARD
RHEOLOGICAL PROPERTIES			
Melt Volume-Flow Rate	33 / *	cm ³ /10min	ISO 1133
Temperature	160 / *	°C	-
	320 / *	°F	-
Load	2.16 / *	kg	-
	4.76 / *	lb	-
THERMAL PROPERTIES			
Melting Temperature, 10°C/min	143 / *	°C	ISO 11357-1/-3
OTHER PROPERTIES			
Density	1.11 / 1.11	kg/m ³	ISO 1183
	0.00111 / 0.00111	g/cm ³	

AVAILABLE GRADES

This grade is available:

- undried with optical brightener (HX 2598 FA)

PACKAGING

Platamid® HX 2598 is delivered in 500 kg sealed big bags (GRVS).

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

PLATAMID®

HX 2598 PELLETS

PROCESSING Web Processing	
DELIVERY FORM Pellets	
SPECIAL CHARACTERISTICS Adhesive	
REGIONAL AVAILABILITY North America, Europe, Asia Pacific, South and Central America, Near East/Africa	