

PLATAMID® M 1422 PELLETS

Platamid® M 1422 Pellets

Copolyamide Hot Melt Adhesive / Extrusion Applications

Platamid® M 1422 Pellets is a standard thermoplastic copolyamide hot melt adhesive available in pellet form and is used in solvent based processes.

Platamid® M 1422 Pellets is a semi-crystalized copolyamide product which has been developed for use in the wire coating industry.

PROPERTIES	DRY / COND	UNIT	TEST STANDARD
RHEOLOGICAL PROPERTIES			
Melt Volume-Flow Rate	30 / *	cm ³ /10min	ISO 1133
Temperature	230 / *	°C	-
	446 / *	°F	-
Load	2.16 / *	kg	-
	4.76 / *	lb	-
THERMAL PROPERTIES			
Melting Temperature, 10°C/min	120 / *	°C	ISO 11357-1/-3

AVAILABLE GRADES

This product is available:

- undried (M 1422 F)
- undried (M 1422/1 F)

PACKAGING

- Platamid® M 1422 F and M 1422/1 F are delivered in 25 kg sealed bags.
- These grades are ready to be processed.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

PROCESSING	
Film Extrusion	
DELIVERY FORM	
Pellets	
SPECIAL CHARACTERISTICS	
Adhesive	
REGIONAL AVAILABILITY	
North America, Europe, Asia Pacific, South and Central America, Near East/Africa	