

## TECHNICAL DATA SHEET

# PLATAMID® HX 2671 PELLET

## COPOLYAMIDE PELLET

PLATAMID® HX 2671 PELLET is a thermoplastic copolyamide hot melt adhesive. This very low melt viscosity, fast re-crystallizing grade is particularly suitable for spraying, manufacturing of webs, nets, mono- and multi-filaments, and films by extrusion. It offers a very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc) and has a very good dry-cleaning resistance and washing resistance up to 40°C. This product is available undried (HX 2671 F).

### TYPE

PA\*

### MAIN APPLICATIONS

- Yarn - Others

### DELIVERY FORM

- Pellets

## RHEOLOGICAL PROPERTIES

PROPERTIES	VALUE	UNIT	TEST STANDARD
Melt volume flow rate (MVR), 160°C / 2.16 kg (320°F / 4.4 lb)	148	cm³/10min	ISO 1133

## THERMAL PROPERTIES

PROPERTIES	VALUE	UNIT	TEST STANDARD
Melting temperature, 10°C/min	122	°C	ISO 11357-1/-3

## PACKAGING

Available packaging:

- 25 kg / 55 lb bags

## SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.