

PLATAMID® M 1943 PELLETS

Platamid® M 1943 Pellets

Copolyamide Hot Melt Adhesive /Extrusion Applications

Platamid® M 1943 Pellets is a standard thermoplastic copolyamide hot melt adhesive available in pellet form. This medium melt viscosity, low re-crystallizing grade, is particularly suitable for manufacturing webs, nets, mono- and multi-filaments and films by extrusion.

Platamid® M 1943 Pellets offer very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc).

PROPERTIES	DRY / COND	UNIT	TEST STANDARD
RHEOLOGICAL PROPERTIES			
Melt Volume-Flow Rate	10 / *	cm ³ /10min	ISO 1133
Temperature	160 / *	°C	-
	320 / *	°F	-
Load	2.16 / *	kg	-
	4.76 / *	lb	-
THERMAL PROPERTIES			
Melting Temperature, 10°C/min	122 / *	°C	ISO 11357-1/-3

AVAILABLE GRADES

This grade is available:

- dried with optical brightener (M 1943 TA)

PACKAGING

Platamid® M 1943 is delivered in 25 kg sealed bags.

This grade are ready to be processed

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

RENEWABLE CARBON CONTENT : 26 % (Internal method)

PLATAMID®

M 1943 PELLETS

PROCESSING Film Extrusion, Melt Spinning, Web Processing	
DELIVERY FORM Pellets	
SPECIAL CHARACTERISTICS Adhesive, Bio-Based	
REGIONAL AVAILABILITY North America, Europe, Asia Pacific, South and Central America, Near East/Africa	