

PLATAMID® HX 2651 PELLETS

Platamid® HX 2651 Pellets

Copolyamide Hot Melt Adhesive / Extrusion Applications

Platamid® HX 2651 Pellets is a standard thermoplastic copolyamide hot melt adhesive available in pellet form. This low melt viscosity grade is particularly suitable for manufacturing webs and nets by extrusion.

Platamid® HX 2651 Pellets offers good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc.) thanks to its amine functionality groups.

PROPERTIES	DRY / COND	UNIT	TEST STANDARD
RHEOLOGICAL PROPERTIES			
Melt Volume-Flow Rate	36 / *	cm ³ /10min	ISO 1133
Temperature	130 / *	°C	-
	266 / *	°F	-
Load	2.16 / *	kg	-
	4.76 / *	lb	-
THERMAL PROPERTIES			
Melting Temperature, 10°C/min	105 / *	°C	ISO 11357-1/-3

AVAILABLE GRADES

This grade is available:

- Platamid® HX 2651 FA Pellets(undried)

PACKAGING

- Platamid® HX 2651 is delivered in 25 kg sealed bags.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

PROCESSING	
Film Extrusion, Melt Spinning, Web Processing	
DELIVERY FORM	
Pellets	
SPECIAL CHARACTERISTICS	
Adhesive	
REGIONAL AVAILABILITY	
North America, Europe, Asia Pacific, South and Central America, Near East/Africa	