

# PLATAMID®

# HX 2627 PELLETS

**Platamid® HX 2627 Pellets**  
Copolyamide Hot Melt Adhesive

**Platamid® HX 2627 Pellets** is a thermoplastic copolyamide hot melt adhesive available in pellet form. This grade has been developed to manufacture hot-melt webs, nets and mono- and multi-filaments. **Platamid® HX 2627 Pellets** offers a very good adhesion to all kinds of textile substrates based on native and synthetic fibers. Additionally **Platamid® HX 2627 Pellets** provide elastomeric properties and high water vapor transmission rate.

PROPERTIES	DRY / COND	UNIT	TEST STANDARD
<b>RHEOLOGICAL PROPERTIES</b>			
Melt Volume-Flow Rate	43 / *	cm <sup>3</sup> /10min	ISO 1133
Temperature	130 / *	°C	-
	266 / *	°F	-
Load	2.16 / *	kg	-
	4.76 / *	lb	-
<b>THERMAL PROPERTIES</b>			
Melting Temperature, 10°C/min	125 / *	°C	ISO 11357-1/-3

## AVAILABLE GRADES

This grade is available:  
- undried with optical brightener ( HX 2627 TA)

## PACKAGING

Platamid® HX 2627 TA is delivered in 500 kg sealed big bags (GRVS).  
This grade is ready to be processed.

## SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

<b>PROCESSING</b>	
Melt Spinning, Web Processing	
<b>DELIVERY FORM</b>	
Pellets	
<b>SPECIAL CHARACTERISTICS</b>	
Adhesive	
<b>REGIONAL AVAILABILITY</b>	
North America, Europe, Asia Pacific, South and Central America, Near East/Africa	