

TECHNICAL DATA SHEET

PLATAMID® M 995 PELLET

COPOLYAMIDE PELLET

PLATAMID® M 995 PELLET is a thermoplastic copolyamide hot melt adhesive. This high melt viscosity grade is particularly suitable for manufacturing of of of films and masterbatches. It offers very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc).

This product is available:

- dried (M 995 T)
- undried (M 995 F)

TYPE

PA*

MAIN APPLICATIONS

- Adhesives - Apparel/Interlining
- Internal Components
- Adhesives - Automotive Interior

DELIVERY FORM

- Pellets

RHEOLOGICAL PROPERTIES

PROPERTIES	VALUE	UNIT	TEST STANDARD
Melt volume flow rate (MVR), 160°C / 2.16 kg (320°F / 4.4 lb)	2	cm³/10min	ISO 1133

THERMAL PROPERTIES

PROPERTIES	VALUE	UNIT	TEST STANDARD
Melting temperature, 10°C/min	144	°C	ISO 11357-1/-3

PACKAGING

Available packaging:

- 25 kg / 55 lb bags

SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.