

PLATAMID® HX 2671 PELLETS

Platamid® HX 2671 Pellets

Copolyamide Hot Melt Adhesive / Extrusion Applications

Platamid® HX 2671 is a standard thermoplastic co-polyamide hot melt adhesive available in pellet form. This very low melt viscosity, fast re-crystallizing grade is particularly suitable for spraying, manufacturing webs, nets, mono- and multi-filaments, and films by extrusion.

Platamid® HX 2671 offers a very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc).

Platamid® HX 2671 has a very good dry-cleaning resistance and washing resistance up to 40°C.

PROPERTIES	DRY / COND	UNIT	TEST STANDARD
RHEOLOGICAL PROPERTIES			
Melt Volume-Flow Rate	148 / *	cm³/10min	ISO 1133
Temperature	160 / *	°C	-
	320 / *	°F	
Load	2.16 / *	kg	-
	4.76 / *	lb	
THERMAL PROPERTIES			
Melting Temperature, 10°C/min	122 / *	°C	ISO 11357-1/-3

AVAILABLE GRADES

This grade is available:

- undried (HX 2671 F)

PACKAGING

Platamid® HX 2671 is delivered in 25 kgs sealed bags.

SHELF LIFE

Two years from the date of delivery. For any use above this limit, please refer to our technical services.

PLATAMID®

HX 2671 PELLETS

PROCESSING Other Extrusion	
DELIVERY FORM Pellets	
SPECIAL CHARACTERISTICS Bio-Based	
REGIONAL AVAILABILITY North America, Europe, Asia Pacific, South and Central America, Near East/Africa	