+135-3858-6433 (GuangDong) +188-1699-6168 (ShangHai) +852-6957-5415 (HongKong)

## RILSAN® D80 NATURAL

RILSAN® D80 NAT is a polyamide 11 powder obtained from renewable resources with an average diameter of 95 - 105um.

RILSAN® D is a range of high performance fine polyamide powders used as multifunctional additives in coatings and varnishes.

The introduction of RILSAN® polyamide powders in formulations is easy thanks to their good dispersion capacity, their reduced Impact on rheology and their low density.

RILSAN® polyamide powders are surface modifiers, specifically designed for texture creation.

Abrasion, scratch, impact resistances and flexibility of coatings, inks and varnishes can be significantly improved using

RILSAN® polyamide powders.

PROPERTIES	VALUE	UNIT	TEST STANDARD
POWDER PROPERTIES			
Particle Size Distribution, Median Size	95 - 105	μm	ISO 13320
	0.00374 - 0.00413	in	
Melting Temperature	186	°C	ISO 1218
	367	°F	
Non Tapped Density	0.47	-	ISO 1068
POWDER COATING PROPERTIES			
Specific Gravity of Coating, 20°C	1.04	-	ISO 1183
Water Absorption, 24h	≤1	%	ISO 62-1

## **APPLICATION PROPERTIES**

- Texturing agent (rough texture) Texture depends on amount of Orgasol® polyamide powder, dry coating thickness and conditions of curing.
- Abrasion & Scratch resistance improvement reinforces the mechanical properties of the coating
- Compatible with most resins used in coating industry suitable for solvent-based, water-based and 100% solid UVcurable systems

## **MAIN APPLICATIONS:**

Coil coating

· Wood coating

· Plastic coating

## **PACKAGING**

This grade is delivered in 20kg bag.

