



**TotalEnergies**

Refining & Chemicals  
Polymers

+135-3858-6433 (GuangDong)  
+188-1699-6168 (ShangHai)  
+852-6957-5415 (HongKong)

## Polyethylene HDPE 56020XP

Technical data sheet  
High Density Polyethylene BLOW MOULDING  
Produced in Europe

### Description

HDPE 56020XP is a very high molecular weight (VHMW) high density polyethylene (HDPE) with high resistance to impact, good chemical resistance and optimized balance between Environmental Stress Cracking Resistance (ESCR) and rigidity. It has been specifically designed for the manufacture of blow molded UN-marked articles (tight head drums, open top drums and jerry-cans) dedicated for the transportation of dangerous goods.

HDPE 56020XP is a pellet grade and contains antioxidants.

### Characteristics

Property	Method	Unit	Typical value (*)
Density	ISO 1183	g/cm <sup>3</sup>	0.952
Melt Flow Rate (190°C/21.6 kg)	ISO 1133/G	g/10 min	1.4
ESCR AntaroX 100%	ASTM D 1693B	h	F <sub>50</sub> > 250
Notched Charpy Impact Resistance 23°C	ISO 179-1	kJ/m <sup>2</sup>	80
Notched Charpy Impact Resistance -30°C	ISO 179-1	kJ/m <sup>2</sup>	55

(\*) Data not intended for specification purposes

Polyethylene