+135-3858-6433 (GuangDong) +188-1699-6168 (ShangHai) +852-6957-5415 (HongKong)



Sinpolene MBW3282/AO

Teknor Apex Asia Pacific PTE. LTD. - Low Density Polyethylene

General Information

Product Description

Sinpolene White MBW3281/AO is a polyethylene-based pure white masterbatch designed specifically for use in tubular film blowing, blow moulding and extrusion of polyolefins. With its extremely high pigment loading, Sinpolene White MBW3281/AO offers high colouring value with excellent quality and performance.

The blue undertone of this masterbatch is attributed by specially selected high performance, fine crystal size rutile titanium dioxide.

Sinpolene White MBW3281/AO is delivered as free flowing pellets for processing convenience.

CHARACTERISTICS

- * Easy processing
- * Good dispersion
- * High opacifying power
- * Excellent whiteness

Executive Williams		
General		
Material Status	Commercial: Active	
Availability	Asia Pacific	
Filler / Reinforcement	Titanium Dioxide, 60% Filler by Weight	
Features	General Purpose	
Uses	• Film	
RoHS Compliance	RoHS Compliant	
Forms	• Pellets	
Processing Method	Film Extrusion	

ASTM & ISO Properties ¹			
Physical	Nominal Value Unit	Test Method	
Density / Specific Gravity	1.73	ASTM D792	
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.0 to 8.0 g/10 min	ASTM D1238	
Moisture Content	< 0.20 %	ASTM D3030	

Recommendation: 3 - 10%

Notes

¹ Typical properties: these are not to be construed as specifications.