



APEX® 1583-60

Teknor Apex Company - Flexible Polyvinyl Chloride

General Information

General

Material Status	• Commercial: Active	
Availability	• Africa & Middle East • Asia Pacific	• Latin America • North America
Uses	• Automotive Applications	• Automotive Interior Parts
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.	
Forms	• Pellets	
Processing Method	• Injection Molding	

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.15		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	1350	psi	ASTM D638
Tensile Elongation (Break)	490	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	55		ASTM D2240

Additional Information

Data Sheet Applies to Color(s) Listed Below:

Black (0409884)

Clear Blue 1 (0381194)

Clear Green 1 (0703014)

Clear Pink 2 (0102575)

10/19 Core

Notes

¹ Typical properties: these are not to be construed as specifications.