



APEX® 3085

Teknor Apex Company - Flexible Polyvinyl Chloride

General Information

General

Material Status	• Commercial: Active		
Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Features	• General Purpose		
Uses	• Film • General Purpose	• Hose • Sheet	• Tubing
Appearance	• Natural Color	• Opaque	
Forms	• Pellets		
Processing Method	• Extrusion		

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.42		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (100% Strain)	1380	psi	ASTM D638
Tensile Strength (Break)	2570	psi	ASTM D638
Tensile Elongation (Break)	360	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength ²	360	lbf/in	ASTM D624
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	91		
Shore A, 15 sec	85		
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	-76.0	°F	ASTM D794
Brittleness Temperature	-14.8	°F	ASTM D746

Notes

¹ Typical properties: these are not to be construed as specifications.

² Die C