



APEX® 3090-H

Teknor Apex Company - Flexible Polyvinyl Chloride

General Information

General

Material Status	• Commercial: Active		
Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Uses	• General Purpose • Hose	• Profiles • Tubing	
Appearance	• Natural Color	• Opaque	
Forms	• Pellets		
Processing Method	• Extrusion		

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.42		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (100% Strain)	1760	psi	ASTM D638
Tensile Strength (Break)	2900	psi	ASTM D638
Tensile Elongation (Break)	350	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength ²	435	lbf/in	ASTM D624
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A	95		
Shore A, 15 sec	90		
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-5.80	°F	ASTM D746

Additional Information

Data Sheet Applies to Color(s) Listed Below:
Natural (0116418)

Notes

¹ Typical properties: these are not to be construed as specifications.

² Die C