



APEX® 3302-90NT

Teknor Apex Company - Flexible Polyvinyl Chloride

General Information

General

Material Status	• Commercial: Active
Availability	• Africa & Middle East • Latin America • Asia Pacific • North America
Additive	• Plasticizer
Features	• Ethylene Oxide Sterilizable • Non-Phthalate - Citrate Plasticizer
Uses	• Medical/Healthcare Applications • Tubing
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.
Appearance	• Clear/Transparent
Forms	• Pellets
Processing Method	• Extrusion

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.27		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	3400	psi	ASTM D638
Tensile Elongation (Break)	340	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec, Hand Held)	90		ASTM D2240
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	10.4	°F	ASTM D746

Additional Information

Data Sheet Applies to Color(s) Listed Below:

Clear Blue B7NP (1057420)

Clear 1 (0706477)

Trans grn 79NP (1084405)

3/2025:sp

Notes

¹ Typical properties: these are not to be construed as specifications.