



# APEX® 3303GRV-80NT1 CBL B8 NP

Teknor Apex Company - Flexible Polyvinyl Chloride

## General Information

| General              |                                                                                                                                                                                                                                      |                                                        |                                                                     |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------|---------------------------------------------------------------------|
| Material Status      | • Commercial: Active                                                                                                                                                                                                                 |                                                        |                                                                     |
| Availability         | • Africa & Middle East<br>• Asia Pacific                                                                                                                                                                                             | • Latin America<br>• North America                     |                                                                     |
| Features             | • ADM Compliant<br>• BPA Free                                                                                                                                                                                                        | • E-beam Sterilizable<br>• Ethylene Oxide Sterilizable | • Non-Phthalate - TOTM Plasticizer<br>• Radiation (Gamma) Resistant |
| Uses                 | • Medical Devices<br>• Medical/Healthcare Applications                                                                                                                                                                               | • Tracheal Tubes<br>• Tubing                           |                                                                     |
| Regulatory Statement | • Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS. |                                                        |                                                                     |
| Forms                | • Pellets                                                                                                                                                                                                                            |                                                        |                                                                     |
| Processing Method    | • Extrusion                                                                                                                                                                                                                          |                                                        |                                                                     |

## ASTM & ISO Properties <sup>1</sup>

| Physical                         | Nominal Value | Unit | Test Method |
|----------------------------------|---------------|------|-------------|
| Density / Specific Gravity       | 1.20          |      | ASTM D792   |
| Mechanical                       | Nominal Value | Unit | Test Method |
| Tensile Strength (100% Strain)   | 2700          | psi  | ASTM D638   |
| Tensile Strength (Break)         | 2850          | psi  | ASTM D638   |
| Tensile Elongation (Break)       | 350           | %    | ASTM D638   |
| Hardness                         | Nominal Value | Unit | Test Method |
| Durometer Hardness               |               |      | ASTM D2240  |
| Shore A, 15 sec, Hand Held       | 80            |      |             |
| Shore A, 15 sec, Operating Stand | 77            |      |             |

## Additional Information

10/19-Imo

## Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.