



APEX® 3304A-80NT

Teknor Apex Company - Flexible Polyvinyl Chloride

General Information

General

Material Status	• Commercial: Active
Availability	• Africa & Middle East • Asia Pacific • Latin America • North America
Features	• BPA Free • Latex Free • Non-Phthalate Plasticizer
Uses	• Medical/Healthcare Applications
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.
Forms	• Pellets
Processing Method	• Extrusion • Injection Molding

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.22		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	2500	psi	ASTM D638
Tensile Elongation (Break)	420	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec, Hand Held)	80		ASTM D2240

Additional Information

Data Sheet Applies to colors listed below:

CLEAR NP (1098290)
 CLEAR 0001 NP (1098297)
 CLEAR 0002 NP (1105853)
 CLEAR BLUE 265 NP (1098302)
 CLEAR BLUE 849 NP (1130711)
 CLEAR BLUE B5 NP (1105120)
 CLEAR BLUE B6 NP (1098303)
 T-BLUE 0015 NP (1140597)
 CLEAR GREEN 158 NP (1126930)

12/2020-lmo

Notes

¹ Typical properties: these are not to be construed as specifications.