



APEX® 3304R-75NT

Teknor Apex Company - Flexible Polyvinyl Chloride

General Information

General

Material Status	• Commercial: Active
Availability	• Africa & Middle East • Asia Pacific • Latin America • North America
Features	• DOTP Blend Plasticizer • Non-Phthalate Plasticizer
Uses	• Medical/Healthcare Applications • Non-specific Food Applications
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.
Forms	• Pellets
Processing Method	• Extrusion

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.19		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	2400	psi	ASTM D638
Tensile Elongation (Break)	420	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec, Hand Held)	75		ASTM D2240

Additional Information

Data Sheet applies to colors listed below:

Clear NP (1100820)
CBL B1 NP (1118165)
CBL B8 NP (1100822)
CBL 518 NP (1094404)
T-GRN 0111 NP (1115828)
CLR BLU B4 NP (1116828)

10/19-Imo

Notes

¹ Typical properties: these are not to be construed as specifications.