



APEX® 3304C-80NT

Teknor Apex Company - Flexible Polyvinyl Chloride

General Information

General

Material Status	• Commercial: Active
Availability	- Africa & Middle East - Asia Pacific - Latin America - North America
Features	- BPA Free - Latex Free - Non-Phthalate Plasticizer
Uses	• Tubing
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.
Forms	• Pellets
Processing Method	• Extrusion

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.22		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	2700	psi	ASTM D638
Tensile Elongation (Break)	400	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A, 15 sec, Hand Held	80		
Shore A, 15 sec, Operating Stand	75		

Additional Information

Data Sheet Applies to Color(s) Listed Below:

Black 1 (1118119)
 Clear NP (1105016)
 Clear Blue 823NP (1123065)
 Clear Blue B4 NP (1127707)
 Clear Blue B5 NP (1113253)
 Clear Blue GB6 NP (1105050)
 White 1 NP (1124815)
 Clear Blue B6 NP (1004459)
 Clear Green 239NP (1098789)
 Clear Blue RB4NP (1140098)

dmm: 10.2024

SP: 1.2021

Notes

¹ Typical properties: these are not to be construed as specifications.