



APEX® 585

Teknor Apex Company - Flexible Polyvinyl Chloride

General Information

Product Description

Applications include tubing, sheet and film, wire coating, and strip doors.

General

Material Status	• Commercial: Active		
Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Features	• General Purpose		
Uses	• Tubing	• Wire Jacketing	
Wire Types	• SPT-1	• SPT-2	
Agency Ratings	• UL 498	• UL 62	
RoHS Compliance	• RoHS Compliant		
Appearance	• Clear/Transparent		
Forms	• Pellets		
Processing Method	• Extrusion		

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.21		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	2500	psi	ASTM D638
Tensile Elongation (Break)	380	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	80		ASTM D2240
Thermal	Nominal Value	Unit	Test Method
Continuous Use Temperature	122	°F	ASTM D794
Brittleness Temperature	-34.6	°F	ASTM D746

Notes

¹ Typical properties: these are not to be construed as specifications.