



APEX® 77-W385-A

Teknor Apex Company - Flexible Polyvinyl Chloride

General Information

Product Description

The Nissan Automotive Specification is Suggested, not Approved.

General

Material Status	• Commercial: Active		
Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Features	• Low Gloss	• Low Temperature Flexibility	
Uses	• Automotive Interior Parts		
RoHS Compliance	• RoHS Compliant		
Automotive Specifications	• NISSAN NES D5311-VT2		
Appearance	• Opaque		
Forms	• Pellets		
Processing Method	• Extrusion		

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.30		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	2250	psi	ASTM D638
Tensile Elongation (Break)	410	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	75		ASTM D2240
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-52.6	°F	ASTM D746

Notes

¹ Typical properties: these are not to be construed as specifications.