



# APEX® 85-J126C-9

Teknor Apex Company - Flexible Polyvinyl Chloride

## General Information

| General              |                                                                                                                                                                                                                                      |                                                              |                                     |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------|-------------------------------------|
| Material Status      | • Commercial: Active                                                                                                                                                                                                                 |                                                              |                                     |
| Availability         | • Africa & Middle East<br>• Asia Pacific                                                                                                                                                                                             | • Latin America<br>• North America                           |                                     |
| Features             | • Flame Retardant<br>• Fungus Resistant                                                                                                                                                                                              | • Microbe Resistant<br>• Plasticized                         | • UV Stabilized                     |
| Uses                 | • Cable Jacketing<br>• Fiber Optic Cable                                                                                                                                                                                             | • Fiber Optic Cable Jacketing<br>• Flame Retardant Jacketing | • Flexible Jacketing<br>• Jacketing |
| Wire Types           | • OFNR                                                                                                                                                                                                                               |                                                              |                                     |
| Agency Ratings       | • UL 1651                                                                                                                                                                                                                            | • UL 444                                                     |                                     |
| Regulatory Statement | • Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS. |                                                              |                                     |
| Appearance           | • Colors Available                                                                                                                                                                                                                   | • Opaque                                                     |                                     |
| Forms                | • Pellets                                                                                                                                                                                                                            |                                                              |                                     |
| Processing Method    | • Wire & Cable Extrusion                                                                                                                                                                                                             |                                                              |                                     |

## ASTM & ISO Properties <sup>1</sup>

| Physical                         | Nominal Value | Unit | Test Method |
|----------------------------------|---------------|------|-------------|
| Density / Specific Gravity       | 1.29          |      | ASTM D792   |
| Mechanical                       | Nominal Value | Unit | Test Method |
| Tensile Strength (Break)         | 3200          | psi  | ASTM D638   |
| Tensile Elongation (Break)       | 340           | %    | ASTM D638   |
| Hardness                         | Nominal Value | Unit | Test Method |
| Durometer Hardness               |               |      | ASTM D2240  |
| Shore C, 10 sec, Hand Held       | 73            |      |             |
| Shore D, 10 sec, Operating Stand | 48            |      |             |
| Thermal                          | Nominal Value | Unit | Test Method |
| Continuous Use Temperature       | 221           | °F   | ASTM D794   |
| Brittleness Temperature          | -18.4         | °F   | ASTM D746   |

### Additional Information

Datasheet Applies to Color Listed Below:  
Natural (0129661)

11/19-lc

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.