



APEX® RE 9003

Teknor Apex Company - Rigid Polyvinyl Chloride

General Information

General

Material Status	• Commercial: Active
Availability	- Africa & Middle East - Asia Pacific - Latin America - North America
Features	• UV Resistant
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.
Appearance	• Opaque
Forms	• Pellets
Processing Method	• Extrusion

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.41		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	411000	psi	ASTM D638
Tensile Strength (Break)	6160	psi	ASTM D638
Tensile Elongation (Break)	80	%	ASTM D638
Flexural Modulus	376000	psi	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
73°F, 0.125 in, Compression Molded	3.8	ft-lb/in	
Drop Impact Resistance ² (73°F, 0.500 in)	2.56	in-lb/mil	ASTM D4226
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 10 sec, Hand Held)	82		ASTM D2240

Additional Information

Data Sheet Applies to Color(s) Listed Below:

Black 628 (1073557)
Brown 1604 (1122160)
Grey 3247 (1122452)
Natural (1073551)
White 1530 (1101450)

10/19 Core

Notes

¹ Typical properties: these are not to be construed as specifications.

² Procedure A