



APEX® RM 8102 NT

Teknor Apex Company - Rigid Polyvinyl Chloride

General Information

General

Material Status	• Commercial: Active
Availability	• Africa & Middle East • Latin America • Asia Pacific • North America
Features	• High Flow
Uses	• Bottles
Agency Ratings	• FDA
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.
Appearance	• Opaque
Forms	• Pellets
Processing Method	• Injection Molding

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.32		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	372000	psi	ASTM D638
Tensile Strength (Break)	7040	psi	ASTM D638
Tensile Elongation (Break)	16	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (73°F, 0.125 in)	0.92	ft-lb/in	ASTM D256
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 10 sec)	80		ASTM D2240

Additional Information

Data Sheet Applies to Color(s) Listed Below:

Clear (1067935)
Clear Blue 1 (1068026)
Grey 3455 (1142991)
Clr Blue 715 (1081667)

10/19 Core

Notes

¹ Typical properties: these are not to be construed as specifications.