



# Cycle-Tek 2390 Natural

Teknor Apex Company - Flexible Polyvinyl Chloride

## General Information

### General

|                      |                                                                                                                                                                                                                                      |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Material Status      | • Commercial: Active                                                                                                                                                                                                                 |
| Availability         | • Africa & Middle East • Latin America<br>• Asia Pacific • North America                                                                                                                                                             |
| Recycled Content     | • Post-Industrial (PIR)/Pre-Consumer, 25%                                                                                                                                                                                            |
| Features             | • Plasticized                                                                                                                                                                                                                        |
| Uses                 | • General Purpose                                                                                                                                                                                                                    |
| Regulatory Statement | • Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS. |
| Appearance           | • Opaque                                                                                                                                                                                                                             |
| Forms                | • Pellets                                                                                                                                                                                                                            |
| Processing Method    | • Extrusion                                                                                                                                                                                                                          |

## ASTM & ISO Properties <sup>1</sup>

| Physical                                        | Nominal Value | Unit | Test Method |
|-------------------------------------------------|---------------|------|-------------|
| Density / Specific Gravity                      | 1.42          |      | ASTM D792   |
| Mechanical                                      | Nominal Value | Unit | Test Method |
| Tensile Strength (Break)                        | 2760          | psi  | ASTM D638   |
| Tensile Elongation (Break)                      | 320           | %    | ASTM D638   |
| Hardness                                        | Nominal Value | Unit | Test Method |
| Durometer Hardness (Shore A, 15 sec, Hand Held) | 90            |      | ASTM D2240  |
| Thermal                                         | Nominal Value | Unit | Test Method |
| Brittleness Temperature                         | -4.00         | °F   | ASTM D746   |

### Additional Information

Data Sheet Applies to Color(s) Listed Below:

Natural (1004566)

2/2024 cw

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.