



FLEXALLOY® 3503RAV-75NT1

Teknor Apex Company - Flexible Polyvinyl Chloride

General Information

General

Material Status	• Commercial: Active	
Availability	• Africa & Middle East • Asia Pacific	• Latin America • North America
Features	• ADM Compliant • BPA Free	• Latex Free • Non-Phthalate - TOTM Plasticizer
Uses	• Medical/Healthcare Applications	
Regulatory Statement	• Due to the frequent updates to regulations, specifically, California Proposition 65, EU REACH SVHCs, and RoHS, please contact Teknor Apex for the most up to date compliance statement, or refer to section 15 of the product SDS.	
Forms	• Pellets	
Processing Method	• Extrusion	

ASTM & ISO Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.19		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (100% Strain)	1230	psi	ASTM D638
Tensile Strength (Break)	2650	psi	ASTM D638
Tensile Elongation (Break)	380	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shore A, 15 sec, Hand Held	75		
Shore A, 15 sec, Operating Stand	70		

Additional Information

Data Sheet applies to color(s) listed below:

CLEAR NP (1131400)

CLEAR BLUE B8 NP (1097915)

2/2020-lmo

Notes

¹ Typical properties: these are not to be construed as specifications.