



# Sinvicomp SGH6500D

Teknor Apex Asia Pacific PTE. LTD. - Flexible Polyvinyl Chloride

## General Information

### General

|                   |                      |
|-------------------|----------------------|
| Material Status   | • Commercial: Active |
| Availability      | • Asia Pacific       |
| Features          | • Good Stiffness     |
| Uses              | • Garden Hose        |
| Forms             | • Pellets            |
| Processing Method | • Extrusion          |

## ASTM & ISO Properties <sup>1</sup>

| Physical                                | Nominal Value | Unit | Test Method   |
|-----------------------------------------|---------------|------|---------------|
| Density / Specific Gravity              | 1.26          |      | ASTM D792     |
| Mechanical                              | Nominal Value | Unit | Test Method   |
| Tensile Strength (Break)                | 1960          | psi  | IEC 60811-1-1 |
| Tensile Elongation <sup>2</sup> (Break) | 320           | %    | IEC 60811-1-1 |
| Hardness                                | Nominal Value | Unit | Test Method   |
| Durometer Hardness (Shore A)            | 69            |      | ASTM D2240    |
| Thermal                                 | Nominal Value | Unit | Test Method   |
| Thermal Stability <sup>3</sup> (374°F)  | > 30          | min  | BS 2782       |

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

<sup>2</sup> 9.8 in/min

<sup>3</sup> Congo Red