



# Scolefin® 61 M 23

## Ravago Manufacturing Europe - Polypropylene

### General Information

#### Product Description

PP Prime compound, light weight, aesthetical surface, excellent balance impact-stiffness, scratch resistant, for interior automotive trims, coloured on request

#### General

Material Status	• Commercial: Active	
Availability	• Europe	• North America
Features	• Good Impact Resistance • Good Scratch Resistance	• Good Stiffness • Pleasing Surface Appearance
Uses	• Automotive Interior Trim	
Appearance	• Colors Available	

### Properties <sup>1</sup>

Physical	Nominal Value	Unit	Test Method
Density	0.980	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	15	g/10 min	ISO 1133
Ash Content (600°C)	10	%	ISO 3451
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	1450	MPa	ISO 527-1
Tensile Stress (Yield)	17.0	MPa	ISO 527-2
Tensile Stress (Break)	12.0	MPa	ISO 527-2
Tensile Strain (Break)	48	%	ISO 527-2
Flexural Modulus	1600	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	25	kJ/m <sup>2</sup>	ISO 180

#### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.