



# Europrene® Latice

XSB LATEX

**406**

Carboxylated Styrene – Butadiene Copolymer

Europrene® Latice 406 is an aqueous dispersion of a modified carboxylated styrene-butadiene copolymer obtained using synthetic anionic emulsifiers. It contains a non staining antioxidant.

Main Properties	Test Method	Unit	Typical Value
Total solid content	ASTM D 1417	% wt	50
Brookfield Viscosity 20 rpm, 25°C	ASTM D 1417	mPa.s	300
Bound styrene	ASTM D 2775	% wt	40
pH	ASTM D 1417		8.0

## Key Features

Europrene® Latice 406 is completely ammonia free. It is a functional polymer with waterproof characteristics. It is designed to provide good binding properties and excellent runnability on high speed impregnation lines.

## Main Applications

Europrene® Latice 406 is mainly used for paper saturation (masking tape) when enhanced waterproofing properties are required.

## Physical Form

At standard condition (T=25 °C P=1 bar) is liquid, color white or milky white.

## Packaging

Europrene® Latice 406 is delivered in road tankers/flexitank (bulk) and IBC (1000 l.).

## Storage Conditions

Store in closed vented tanks or in a covered place in sealed packaging, away from sunlight and heat sources, at temperature between +5°C and +40°C. The water dispersion should be stirred before use. The shelf life is 6 months minimum.

