



## ELVAX™ CE9619-1

### Ethylene Vinyl Acetate Copolymer

#### General Information

**Product Description** ELVAX™ CE9619-1 is an extrudable ethylene-vinyl acetate copolymer resin concentrate designed to modify the surface properties of films or coatings of ELVAX™ resins or other compatible polymers. This is a concentrated masterbatch product and is designed to be blended with the resin to be modified. This concentrate contains 20 wt.% antiblock and 7 wt.% slip additives. It is available in pellet form for use in conventional extrusion equipment designed to process polyethylene resins.

#### Status

**Material Status** Commercial: Active

#### Typical Characteristics

**Composition** 73% By Weight of an 18 % By Weight Vinyl Acetate comonomer content resin

Thermal Stabilizer: BHT antioxidant  
7% By Weight Amide based slip agent  
20% By Weight Inorganic antiblock agent

**Features** This is a concentrated masterbatch product and is designed to be blended with other polymers. This resin is not intended to be extruded in its pure form.

**Applications** This resin is designed to modify the surface properties of films or coatings of ELVAX™ resins or other compatible polymers.

#### Typical Properties

Physical	Nominal Values	Test Method(s)	
*Density ( )	1.06 g/cm <sup>3</sup>	ASTM D792	ISO 1183
*Melt Flow Index ( 190°C/2.16kg)	3.8 g/10 min	ASTM D1238	ISO 1133
Thermal	Nominal Values	Test Method(s)	
*Melting Point( DSC)	87 °C ( 188.6 °F )	ASTM D3418	ISO 3146

#### Processing Information

\*Maximum Processing Temperature 235 °C ( 455 °F )

**General Processing Information** ELVAX™ resins can be used in conventional extrusion equipment designed to process polyethylene resins. However, corrosion-protected barrels, screws, adapters, and dies are recommended, since, at sustained melt temperatures above 235°C (455°F) ethylene-vinyl acetate (EVA) resins may thermally degrade and release corrosive by-products.

**FDA Status Information** ELVAX™ CE9619-1 resin concentrate is designed to modify the surface properties of films or coatings of ELVAX™ Resins or other compatible polymers. This is a concentrated masterbatch product and is designed to be blended with the resin to be modified.



ELVAX™ CE9619-1 resin concentrate complies with Food and Drug Administration Regulation 21 CFR 177.1350(a)(1) - - Ethylene-vinyl acetate copolymers, subject to the limitations and requirements therein. This Regulation describes polymers that may be used in contact with food, subject to the finished food-contact article meeting the extractive limitations under the intended conditions of use, as shown in paragraph (b)(1) of the Regulation.

The information and certifications provided herein are based on data we believe to be reliable, to the best of our knowledge. The information and certifications apply only to the specific material designated herein as sold by Dow and do not apply to use in any process or in combination with any other material. They are provided at the request of and without charge to our customers. Accordingly, Dow cannot guarantee or warrant such certifications or information and assumes no liability for their use.

**Regulatory Information**

For information on regulatory compliance outside of the U.S.A., consult your local Dow representative.

**Safety & Handling**

For information on appropriate Handling & Storage of this polymeric resin, please refer to the material Safety Data Sheet.

A Product Safety Bulletin, material Safety Data Sheet, and/or more detailed information on extrusion processing and/or compounding of this polymeric resin for specific applications are available from your Dow representative.

