

**Makrolon® ET UV112**

 Covestro - Polycarbonates - *Polycarbonate*
**General Information**
**Product Description**

MVR (300°C/1.2 kg) 13 cm³/10 min; high viscosity; Corrugated Sheets; special grade for the coextrusion of Makrolon ET base resins; with anti stick properties for finished sheets; available in color code 551340 only

**General**

|                   |                        |                   |                 |
|-------------------|------------------------|-------------------|-----------------|
| Material Status   | • Commercial: Active   |                   |                 |
| Availability      | • Africa & Middle East | • Europe          | • North America |
|                   | • Asia Pacific         | • Latin America   |                 |
| Features          | • High Viscosity       |                   |                 |
| Uses              | • Corrugated Sheet     | • Sheet           |                 |
| RoHS Compliance   | • RoHS Compliant       |                   |                 |
| Processing Method | • Coextrusion          | • Sheet Extrusion |                 |

**Properties <sup>1</sup>**

| Physical                                   | Nominal Value | Unit      | Test Method |
|--|---------------|-----------|-------------|
| Density (73°F)                             | 1.20          | g/cm³     | ISO 1183    |
| Melt Volume-Flow Rate (MVR) (300°C/1.2 kg) | 13            | cm³/10min | ISO 1133    |

**Notes**
<sup>1</sup> Typical properties: these are not to be construed as specifications.
