

AuroraFlex™ 3467SL-PMC

 Aurora Material Solutions, LLC - *Polyvinyl Chloride*
General Information
Product Description

A PVC based compound, suitable for general purpose extrusion applications with good scratch and surface abrasion resistance.

Note: Additional custom color matching is available upon request.

General

Material Status	• Commercial: Active
Availability	• Africa & Middle East • Europe • North America • Asia Pacific • Latin America
Features	• Abrasion Resistant • General Purpose • Good Scratch Resistance
Uses	• General Purpose
Appearance	• Colors Available
Processing Method	• Extrusion

Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.39 to 1.45		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Taber Abrasion Resistance (2000 Cycles, 1000 g, H-18 Wheel)	< 400	mg	ASTM D1044
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength	1900	psi	ASTM D412
Tensile Elongation (Break)	350	%	ASTM D412
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	64 to 70		ASTM D2240

Notes
¹ Typical properties: these are not to be construed as specifications.
