

**AuroraFlex™ G-93-016AGH**

 Aurora Material Solutions, LLC - *Polyvinyl Chloride*
**General Information**
**Product Description**

A RoHS Compliant, Flame Retardant 60/75°C Jacketing Compound

Note: Additional custom color matching is available upon request.

**General**

Material Status	• Commercial: Active
Availability	• Africa & Middle East • Europe • North America • Asia Pacific • Latin America
Additive	• Flame Retardant
Features	• Flame Retardant
Uses	• Jacketing
RoHS Compliance	• RoHS Compliant
Appearance	• Colors Available
Processing Method	• Compounding

**Properties <sup>1</sup>**

	Nominal Value	Unit	Test Method
<b>Physical</b>			
Density / Specific Gravity	1.37 to 1.43		ASTM D792
<b>Elastomers</b>			
Tensile Strength	2800	psi	ASTM D412
Tensile Elongation (Break)	300	%	ASTM D412
<b>Hardness</b>			
Durometer Hardness (Shore A, 15 sec)	87 to 93		ASTM D2240
<b>Thermal</b>			
Cold Bend	-4	°F	UL 1581
<b>Flammability</b>			
Oxygen Index	31	%	ASTM D2863

**Notes**
<sup>1</sup> Typical properties: these are not to be construed as specifications.
