

AuroraFlex™ RX 12668 B Black

Aurora Material Solutions, LLC - *Polyvinyl Chloride*
General Information
Product Description

co-extrusion

Made in Canada

General

Material Status	<ul style="list-style-type: none"> Commercial: Active 		
Availability	<ul style="list-style-type: none"> Africa & Middle East Asia Pacific 	<ul style="list-style-type: none"> Europe Latin America 	<ul style="list-style-type: none"> North America
Uses	<ul style="list-style-type: none"> Aerospace Applications Agricultural Applications Appliances Automotive Applications Capstock 	<ul style="list-style-type: none"> Consumer Applications Electrical/Electronic Applications Energy Storage Film Footwear 	<ul style="list-style-type: none"> Furniture Medical/Healthcare Applications Personal Care Sheet
Appearance	<ul style="list-style-type: none"> Black 		
Processing Method	<ul style="list-style-type: none"> Coextrusion 	<ul style="list-style-type: none"> Extrusion 	

Properties ¹

	Nominal Value	Unit
Physical		
Density / Specific Gravity	1.26	
Mechanical		
Tensile Strength	1620	psi
Tensile Elongation (Break)	390	%
Hardness		
Durometer Hardness (Shore A, 15 sec)	66	
Thermal		
Brittleness Temperature	-43.6	°F

Notes
¹ Typical properties: these are not to be construed as specifications.
