

AuroraTec™ AP2502ANT1000

Aurora Material Solutions, LLC - Polyvinyl Chloride

General Information
Product Description

A rigid PVC powder, extrusion compound with excellent properties and processing designed for interior applications, especially substrates.

General

Material Status	• Commercial: Active		
Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Features	• Excellent Processability • Good Rigidity		
Uses	• Agricultural Applications • Appliances • Automotive Applications • Consumer Applications • Electrical/Electronic Applications	• Fencing & Decking • Film • Medical/Healthcare Applications • Outdoor Applications • Rail Applications	• Sheet • Spas • Windows & Doors
Forms	• Powder		
Processing Method	• Extrusion		

Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.41		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	503000	psi	ASTM D638
Tensile Strength	6340	psi	ASTM D638
Flexural Modulus	457000	psi	ASTM D790
Flexural Strength	11300	psi	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	6.9	ft·lb/in	ASTM D256
Dart Impact ²			ASTM D4226
Procedure A		1 in·lb/mil	
Procedure B		> 4 in·lb/mil	
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	77		ASTM D2240
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (264 psi, Annealed)	165	°F	ASTM D648
CLTE - Flow	3.7E-5	in/in/°F	ASTM D696

Notes
¹ Typical properties: these are not to be construed as specifications.

² Min Failure
