

AuroraTec™ RR 5090UV Clear

Aurora Material Solutions, LLC - Rigid Polyvinyl Chloride

General Information

Product Description

A Rigid transparent PVC for profile extrusion.

Made in Canada

General

Material Status	• Commercial: Active		
Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Additive	• Impact Modifier		
Features	• Good Rigidity	• UV Resistant	
Uses	• Agricultural Applications • Appliances • Automotive Applications	• Consumer Applications • Electrical/Electronic Applications • Rail Applications	• Sheet • Windows & Doors
Appearance	• Clear/Transparent		
Processing Method	• Profile Extrusion		

Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.33		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	400000	psi	ASTM D638
Tensile Strength	6900	psi	ASTM D638
Flexural Strength	12000	psi	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (73°F, 0.126 in)	2.0	ft·lb/in	ASTM D256
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D, 15 sec)	80		ASTM D2240
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (264 psi, Annealed)	158	°F	ASTM D648

Notes

¹ Typical properties: these are not to be construed as specifications.

