

Manner Flexible PVC M1695 NAT601

Manner Polymers - Flexible Polyvinyl Chloride

General Information

Product Description

Recommended Applications: 105°C General Purpose Injection Molding Compound. This product complies with the European Union Restriction on Hazardous Substances (RoHS) directive. UL Recognized UL94 V0 Compound.

General

Material Status	<ul style="list-style-type: none"> Commercial: Active
Availability	<ul style="list-style-type: none"> North America
Features	<ul style="list-style-type: none"> General Purpose
Uses	<ul style="list-style-type: none"> General Purpose
Appearance	<ul style="list-style-type: none"> Natural Color
Processing Method	<ul style="list-style-type: none"> Injection Molding

Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.41 to 1.45		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus - 100% Secant ²	2080	psi	ASTM D638
Tensile Strength ²	2340	psi	ASTM D638
Tensile Elongation ² (Break)	190	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A, 15 sec)	92 to 95		ASTM D2240
Flammability	Nominal Value	Unit	Test Method
Flame Rating			UL 94
0.06 in		V-0	
0.12 in		V-0	
Oxygen Index	33	%	ASTM D2863

Notes

¹ Typical properties: these are not to be construed as specifications.

² Unaged Dumbbells

