

Manner Flexible PVC M1584

Manner Polymers - Flexible Polyvinyl Chloride

General Information

Product Description

Recommended Applications: Lead-free general purpose injection molding compound. Manner M1584 is UL recognized under QMFZ8 and QMFZ2. This product complies with the European Union Restriction on Hazardous Substances (RoHS) directive.

General

Material Status	• Commercial: Active
Availability	• North America
Features	• General Purpose • Low (to None) Lead Content
Uses	• General Purpose
Agency Ratings	• UL QMFZ2 • UL QMFZ8
Processing Method	• Injection Molding

Properties ¹

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.42 to 1.46		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus - 100% Secant ²	1690	psi	ASTM D638
Tensile Strength ²	1910	psi	ASTM D638
Tensile Elongation ² (Break)	170	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore C)	81 to 87		ASTM D2240
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	26	%	ASTM D2863

Notes

¹ Typical properties: these are not to be construed as specifications.

² Unaged Dumbbells: .03 inches

