

## Manner Flexible PVC X3617

Manner Polymers - Flexible Polyvinyl Chloride

### General Information

#### Product Description

General Purpose profile extrusion compound. This product complies with the European Union Restriction on Hazardous Substances (RoHS) directive.

#### General

Material Status	<ul style="list-style-type: none"> <li>Commercial: Active</li> </ul>
Availability	<ul style="list-style-type: none"> <li>North America</li> </ul>
Features	<ul style="list-style-type: none"> <li>General Purpose</li> </ul>
Uses	<ul style="list-style-type: none"> <li>Profiles</li> </ul>
RoHS Compliance	<ul style="list-style-type: none"> <li>RoHS Compliant</li> </ul>
Processing Method	<ul style="list-style-type: none"> <li>Profile Extrusion</li> </ul>

### Properties <sup>1</sup>

Physical	Nominal Value	Unit	Test Method
Density / Specific Gravity	1.32 to 1.36		ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength			ASTM D638
--	2100	psi	
100% Strain	1900	psi	
Tensile Elongation (Break)	230	%	ASTM D638
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore C)	90		ASTM D2240

### Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

