

THERMOLAST® K TF8WCS (Series: DW/CS)

KRAIBURG TPE - *Thermoplastic Elastomer*

General Information

Product Description

Sealing applications in the drinking water sector with adhesion to PP

Typical applications

- Seals, functional and design elements in sanitary sector

Material advantages

- Adhesion to PP
- Plasticizer free
- Optimized compression set
- Thermoplastic alternative to elastomers
- Resistance to microbes

Regulations / Approvals

- Regulation (EU) No 10/2011
- DVGW Arbeitsblatt W270
- ACS (DGS/VS4 n° 200/232)

General

Material Status	• Commercial: Active		
Availability	• Africa & Middle East • Asia Pacific	• Europe • Latin America	• North America
Features	• Good Adhesion	• Good Compression Set	• Microbe Resistant
Uses	• Seals		
Agency Ratings	• ACS DGS/VS 4 n° 2000-232	• DVGW W270	• EU 10/2011
Appearance	• Natural Color		
Processing Method	• Extrusion	• Injection Molding	

Properties ¹

Physical	Nominal Value	Unit	Test Method
Density	0.930	g/cm ³	ISO 1183
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress ² (Break)	2320	psi	ISO 37
Tensile Elongation ² (Break)	600	%	ISO 37
Tear Strength ³	154	lbf/in	ISO 34-1
Compression Set ⁴			ISO 815
73°F, 72 hr	20	%	
158°F, 24 hr	75	%	
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	76		ISO 48-4

Notes

¹ Typical properties: these are not to be construed as specifications.

² Type S2, 7.9 in/min

³ Method Bb, Angle (Nicked)

⁴ Method A

